



*ProLume*  
◀ T2 Mini Spirals

COMPACTS

## *ProLume*® T2 Mini Spirals

### Energy Efficient

- Maximum light distribution achieved through compact design
- Save up to 80% in energy costs compared to incandescent lamps
- Tri-phosphor coating enhances lumen efficacy and color rendering

### Technical Data

- Electronic Instant Start Ballast
- 120 Volt, 60Hz
- 5°F Minimum Starting Temperature
- Nickel-plated brass base

### Broad Assortment

- 5, 9, 13 and 18 watt
- 2700, 4100, 5000K
- 5, 9 and 13 watt available in E12 and E26 base
- 18 watt available in E26 base

### Long Life

- 10,000 Hours Average Rated Life

### Applications

- Table lamps
- Ceiling fixtures
- Down lighting

**Halco**  
LIGHTING TECHNOLOGIES

### New Ultra Compact Design for Low Profile Applications.

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at [halcolighting.com](http://halcolighting.com).

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



*where there's light,  
there's halco*™

(800) 677-3334  
[halcolighting.com](http://halcolighting.com)

Bulb Type	Watts	Base	Item #	Product Code	Description	Inner/Master	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Avg Rated Life	MOL
<b>T2 MINI-SPIRALS</b>												
T2	5	Med	45010	PL5SE/27	Warm White	10/60	2700	82	250	25W	10,000	3-1/2"
T2	5	Cand	45011	PL5SE/27/E12	Warm White	10/60	2700	82	250	25W	10,000	3-1/2"
T2	5	Med	45016	PL5SE/41	Cool White	10/60	4100	82	250	25W	10,000	3-1/2"
T2	5	Cand	45017	PL5SE/41/E12	Cool White	10/60	4100	82	250	25W	10,000	3-1/2"
T2	5	Med	45018	PL5SE/50	Natural White	10/60	5000	82	250	25W	10,000	3-1/2"
T2	5	Cand	45019	PL5SE/50/E12	Natural White	10/60	5000	82	250	25W	10,000	3-1/2"
T2	9	Med	45030	PL9SE/27	Warm White	10/60	2700	82	500	40W	10,000	4"
T2	9	Cand	45031	PL9SE/27/E12	Warm White	10/60	2700	82	500	40W	10,000	4"
T2	9	Med	45036	PL9SE/41	Cool White	10/60	4100	82	500	40W	10,000	4"
T2	9	Cand	45037	PL9SE/41/E12	Cool White	10/60	4100	82	500	40W	10,000	4"
T2	9	Med	45038	PL9SE/50	Natural White	10/60	5000	82	500	40W	10,000	4"
T2	9	Cand	45039	PL9SE/50/E12	Natural White	10/60	5000	82	500	40W	10,000	4"
T2	13	Med	45050	PL13SE/27/T2	Warm White	10/60	2700	82	800	60W	10,000	4-3/16"
T2	13	Cand	45051	PL13SE/27/T2/E12	Warm White	10/60	2700	82	800	60W	10,000	4-1/8"
T2	13	Med	45056	PL13SE/41/T2	Cool White	10/60	4100	82	800	60W	10,000	4-3/16"
T2	13	Cand	45057	PL13SE/41/T2/E12	Cool White	10/60	4100	82	800	60W	10,000	4-1/8"
T2	13	Med	45058	PL13SE/50/T2	Natural White	10/60	5000	82	800	60W	10,000	4-3/16"
T2	13	Cand	45059	PL13SE/50/T2/E12	Natural White	10/60	5000	82	800	60W	10,000	4-1/8"
T2	18	Med	45062	PL18SE/27/T2	Warm White	10/60	2700	82	1100	75W	10,000	4-9/16"
T2	18	Med	45065	PL18SE/41/T2	Cool White	10/60	4100	82	1100	75W	10,000	4-9/16"
T2	18	Med	45066	PL18SE/50/T2	Natural White	10/60	5000	82	1100	75W	10,000	4-9/16"

**NEW ITEM!**

**(Hg)** Hg-LAMP CONTAINS MERCURY,  
MANAGE IN ACCORD WITH DISPOSAL LAWS.

Not for use on dimming circuits, timing devices, photo sensors or occupancy sensors.  
This device is not intended for use with emergency exit fixtures.